

Printing date 23.06.2009

Revision: 23.06.2009

1 Identification of the substance/preparation and of the company/undertaking

- · Product details
- Trade name: vinyl acetate
- Manufacturer/Supplier: Petrochem Middle East FZE PO Box 17028, Jebel Ali Free Zone Dubai, UAE Ph +971 4 8839222; Fax +971 4 8834133
- Further information obtainable from: Product safety department.
- · Information in case of Emergency Product safety department.

2 Composition/information on ingredients

- · Chemical characterization:
- *CAS No. Description* 108-05-4 vinyl acetate
- · Identification number(s)
- EINECS Number: 203-545-4
- Index number: 607-023-00-0

3 Hazards identification

· Hazard description:



F Highly flammable

• *Information concerning particular hazards for human and environment: R 11 Highly flammable.*

4 First aid measures

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.

5 Fire-fighting measures

- · Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- Protective equipment: No special measures required.

6 Accidental release measures

- · Person-related safety precautions: Wear protective equipment. Keep unprotected persons away.
- Measures for environmental protection:
- Do not allow product to reach sewage system or any water course.
- Inform respective authorities in case of seepage into water course or sewage system.
- Do not allow to enter sewers/ surface or ground water.
- · Measures for cleaning/collecting:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

(Contd. on page 2)

Printing date 23.06.2009

Revision: 23.06.2009

Trade name: vinyl acetate

Ensure adequate ventilation.

(Contd. of page 1)

7 Handling and storage

- · Handling:
- *Information for safe handling:* Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- *Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.*

· Storage:

- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

8 Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

· Ingredients with limit values that require monitoring at the workplace:

108-05-4 vinyl acetate

	-	
REL (USA)	Short-term value: C 15* mg/m ³ , C 4* ppm	
	*15-min	
TLV (USA)	Short-term value: 53 mg/m³, 15 ppm	
	*15-min Short-term value: 53 mg/m ³ , 15 ppm Long-term value: 35 mg/m ³ , 10 ppm	

• Additional information: The lists valid during the making were used as basis.

· Personal protective equipment:

- · General protective and hygienic measures: Wash hands before breaks and at the end of work.
- Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:



Tightly sealed goggles

(Contd. on page 3)

UAE

Printing date 23.06.2009

Revision: 23.06.2009

Trade name: vinyl acetate

(Contd. of page 2)

General Information	
Form:	Fluid
Colour:	Colourless
Odour:	Sweetish
Change in condition Melting point/Melting range	:-93 2°C
Boiling point/Boiling range:	
Flash point:	-8°C
Ignition temperature:	425°C
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapou mixtures are possible.
Explosion limits:	
Lower:	2.6 Vol %
Upper:	13.4 Vol %
Vapour pressure at 20°C:	111 hPa
Density at 20°C:	0.93 g/cm ³
Solubility in / Miscibility with water at 20°C:	20 g/l

10 Stability and reactivity

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

· Dangerous reactions No dangerous reactions known.

· Dangerous decomposition products: No dangerous decomposition products known.

11 Toxicological information

• Acute toxicity:

· LD/LC50 values relevant for classification:

Oral LD50 2920 mg/kg (rat)

Dermal LD50 2335 mg/kg (rabbit)

- · Primary irritant effect:
- on the skin: No irritant effect.
- on the eye: No irritating effect.
- Sensitization: No sensitizing effects known.

12 Ecological information

· General notes:

Water hazard class 2 (German Regulation) (Assessment by list): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

(Contd. on page 4)

UAF

Printing date 23.06.2009

Revision: 23.06.2009

Trade name: vinyl acetate

(Contd. of page 3)

13 Disposal considerations

· Product:

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

14 Transport information

· Land transport ADR/RID (cross-border)



· ADR/RID class:	3 Flammable liquids.
· Danger code (Kemler):	339
· UN-Number:	1301
· Packaging group:	II

3

- · Packaging group: · Hazard label:
- · Description of goods: 1301 VINYL ACETATE, STABILIZED

• Maritime transport IMDG:



3	
· IMDG Class:	3
· UN Number:	1301
· Label	3
· Packaging group:	II
• EMS Number:	F-E,S-D
· Marine pollutant:	No
• Proper shipping name:	VINYL ACETATE, STABILIZED

· Air transport ICAO-TI and IATA-DGR:



· Proper shipping name: VINYL ACETATE, STABILIZED

15 Regulatory information

· Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

(Contd. on page 5)

UAE

Printing date 23.06.2009

Revision: 23.06.2009

Trade name: vinyl acetate

(Contd. of page 4)

UAE

· Code letter and hazard designation of product:



F Highly flammable

• *Risk phrases:* 11 Highly flammable.

· Safety phrases:

- 2 Keep out of the reach of children.
- 16 Keep away from sources of ignition No smoking.
- 23 Do not breathe gas/fumes/vapour/spray (appropriate wording to be specified by the manufacturer).
- 29 Do not empty into drains.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing MSDS: Product safety department

· Contact: Mr. Menon